

WS-12-250-DC

Netonix-02

Total 0W 250W

TIME NOT SET

Input Voltage: 24.1 V

Input Current: 0.3 A

404.36
TX Kbps

15.30
RX Kbps

35
TX pps

13
RX pps

Status

Ports

VLANs

LAG

STP

QoS

Tools ▾

ERPS

Power

Device ▾

Utilities ▾

Save/Apply

Log

☒ Switch ☐ Linux ☐ All

Clear

Email

Dec 31 20:11:08 UI: Log cleared by admin (::ffff:172.20.43.250)

Dec 31 20:11:10 Port: link state changed to 'down' on port 2

Dec 31 20:11:10 STP: MSTI0: New root on port 3, root path cost is 0, root bridge id is 32768.00-00-00-00-00-11

Dec 31 20:11:10 STP: msti 0 set port 2 to discarding

Dec 31 20:11:10 STP: MSTI1: New root on port 3, root path cost is 0, root bridge id is 0.00-00-00-00-00-00

Dec 31 20:11:10 STP: msti 1 set port 2 to discarding

Dec 31 20:11:10 STP: msti 0 set port 3 to learning

Dec 31 20:11:10 STP: msti 0 set port 3 to forwarding

Dec 31 20:11:10 STP: msti 1 set port 3 to learning

Dec 31 20:11:10 STP: msti 1 set port 3 to forwarding